

# American Lumber Standard Committee, Incorporated®

T.F. Brodie, Chairman  
L.N. Belden, Vice Chairman  
L.N. Belden, Treasurer  
D.E. Kretschmann, President

7470 New Technology Way, Suite F  
Frederick, Maryland 21703  
Telephone: 301.972.1700  
Fax: 301.540.8004  
E-Mail: [alsc@alsc.org](mailto:alsc@alsc.org)

## ACCREDITED AGENCIES FOR SUPERVISORY AND LOT INSPECTION OF DENSIFIED FUEL

January 2018

*(this list supersedes all previous lists)*

Agencies accredited by the Board of Review of the American Lumber Standard Committee, Incorporated and typical quality marks.

### Interpreting a Quality Mark

The diagram shows a quality mark for PFI Graded Fuel. It includes a logo for the Pellet Fuels Institute (PFI) with the text 'PFI GRADED FUEL'. Below the logo, it specifies 'PFI Densified Fuel Grade: Premium' and 'Mill Registration # 00000'. A table of 'Grade Requirements' lists various specifications such as Bulk Density, Diameter, Durability, Fines, Ash Content, Length, Moisture, and Chlorides. Below the table is a section for 'Manufacturers Guaranteed Analysis' with fields for Type of Material, Additives, Minimum Higher Heating Value, and Other Manufacturers Guarantees. At the bottom, there is a box for 'Approved Auditing Agency Logo Displayed Here' and a footer with the website [www.pelletheat.org](http://www.pelletheat.org).

Grade Requirements:	
Bulk Density:	40–46 lbs/ft <sup>3</sup>
Diameter:	.230–.285 in/5.84–7.25 mm
Durability:	≥96.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1% >1.5 in.
Moisture:	≤8.0%
Chlorides:	≤300 ppm

**Manufacturers Guaranteed Analysis:**

Type of Material:

Additives:


Minimum Higher Heating Value (as received):

Other Manufacturers Guarantees:

Required Quality Mark elements:

- (a) Manufacturer's Registration Number
- (b) Applicable Pellet Fuels Institute Densified Fuel Grade (Premium, Standard, or Utility)
- (c) Manufacturer's Guaranteed Analysis
- (d) The identifying symbol or logo of the accredited agency and the Pellet Fuels Institute

**ACCREDITED AGENCIES ADDRESSES AND EXAMPLES OF TYPICAL QUALITY MARK(S)**




**PFI Densified Fuel Grade: Premium**  
**Mill Registration # 03000**  
**Grade Requirements:**

Bulk Density:	40–46 lbs/ft <sup>3</sup>
Diameter:	.230–.285 in/5.84–7.25 mm
Durability:	≥96.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1% >1.5 in.
Moisture:	≤8.0%
Chlorides:	≤300 ppm

**Manufacturers Guaranteed Analysis:**

Type of Material: \_\_\_\_\_  
 Additives: \_\_\_\_\_  
 Minimum Higher Heating Value (as received): \_\_\_\_\_  
 Other Manufacturers Guarantees: \_\_\_\_\_




© For more information, please visit the PFI website at [www.pelletheat.org](http://www.pelletheat.org).

**Conway & Robison, LLC**

P.O. Box 1508  
 Sharpsburg, GA 30277

678.642.4036  
 Fax: 770.234.5837

e-mail: [jason@cr-inspect.com](mailto:jason@cr-inspect.com)




**PFI Densified Fuel Grade: Premium**  
**Mill Registration # 10000**  
**Grade Requirements:**

Bulk Density:	40–46 lbs/ft <sup>3</sup>
Diameter:	.230–.285 in/5.84–7.25 mm
Durability:	≥96.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1% >1.5 in.
Moisture:	≤8.0%
Chlorides:	≤300 ppm

**Manufacturers Guaranteed Analysis:**

Type of Material: \_\_\_\_\_  
 Additives: \_\_\_\_\_  
 Minimum Higher Heating Value (as received): \_\_\_\_\_  
 Other Manufacturers Guarantees: \_\_\_\_\_




© For more information, please visit the PFI website at [www.pelletheat.org](http://www.pelletheat.org).

**Pacific Lumber Inspection Bureau**

909 S. 336<sup>th</sup> Street, Suite 203  
 Federal Way, WA 98003

253.835.3344  
 Fax: 253.835.3371

e-mail: [info@plib.org](mailto:info@plib.org)




**PFI Densified Fuel Grade: Premium**  
**Mill Registration # 05000**  
**Grade Requirements:**

Bulk Density:	40–46 lbs/ft <sup>3</sup>
Diameter:	.230–.285 in/5.84–7.25 mm
Durability:	≥96.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1% >1.5 in.
Moisture:	≤8.0%
Chlorides:	≤300 ppm

**Manufacturers Guaranteed Analysis:**

Type of Material: \_\_\_\_\_  
 Additives: \_\_\_\_\_  
 Minimum Higher Heating Value (as received): \_\_\_\_\_  
 Other Manufacturers Guarantees: \_\_\_\_\_




© For more information, please visit the PFI website at [www.pelletheat.org](http://www.pelletheat.org).

**PFS Corporation**

1507 Matt Pass  
 Cottage Grove, WI 53527

608.839.1013  
 Fax: 608.839.1014

e-mail: [pellets@pfscorporation.com](mailto:pellets@pfscorporation.com)




**PFI Densified Fuel Grade: Premium**  
**Mill Registration # 14000**  
**Grade Requirements:**

Bulk Density:	40–46 lbs/ft <sup>3</sup>
Diameter:	.230–.285 in/5.84–7.25 mm
Durability:	≥96.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1% >1.5 in.
Moisture:	≤8.0%
Chlorides:	≤300 ppm

**Manufacturers Guaranteed Analysis:**

Type of Material: \_\_\_\_\_  
 Additives: \_\_\_\_\_  
 Minimum Higher Heating Value (as received): \_\_\_\_\_  
 Other Manufacturers Guarantees: \_\_\_\_\_




© For more information, please visit the PFI website at [www.pelletheat.org](http://www.pelletheat.org).

**Southern Pine Inspection Bureau**

4555 Spanish Trail  
 Pensacola, FL 32504

850.434.5011  
 Fax: 850.434.5388

e-mail: [spib@spib.org](mailto:spib@spib.org)




**PFI Densified Fuel Grade: Premium**  
**Mill Registration # 16000**  
**Grade Requirements:**

Bulk Density:	40–46 lbs/ft <sup>3</sup>
Diameter:	.230–.285 in/5.84–7.25 mm
Durability:	≥96.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1% >1.5 in.
Moisture:	≤8.0%
Chlorides:	≤300 ppm

**Manufacturers Guaranteed Analysis:**

Type of Material: \_\_\_\_\_  
 Additives: \_\_\_\_\_  
 Minimum Higher Heating Value (as received): \_\_\_\_\_  
 Other Manufacturers Guarantees: \_\_\_\_\_




© For more information, please visit the PFI website at [www.pelletheat.org](http://www.pelletheat.org).

**Timber Products Inspection**

1641 Sigman Rd.  
 Conyers, GA 30012

218.428.3583  
 Fax: 770.922.1290

e-mail: [cwiberg@tpinspection.com](mailto:cwiberg@tpinspection.com)




**PFI Densified Fuel Grade: Premium**  
**Mill Registration # 17000**  
**Grade Requirements:**

Bulk Density:	40–46 lbs/ft <sup>3</sup>
Diameter:	.230–.285 in/5.84–7.25 mm
Durability:	≥96.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1% >1.5 in.
Moisture:	≤8.0%
Chlorides:	≤300 ppm

**Manufacturers Guaranteed Analysis:**

Type of Material: \_\_\_\_\_  
 Additives: \_\_\_\_\_  
 Minimum Higher Heating Value (as received): \_\_\_\_\_  
 Other Manufacturers Guarantees: \_\_\_\_\_



© For more information, please visit the PFI website at [www.pelletheat.org](http://www.pelletheat.org).

**West Coast Lumber Inspection Bureau**

P.O. Box 23145  
 Portland, OR 97281-3145

503.639.0651  
 Fax: 503.684.8928

e-mail: [info@wclib.org](mailto:info@wclib.org)

The following laboratories are accredited for the analysis of densified fuel samples in accordance with the Pellet Fuel Institute *Standard Specification for Residential/Commercial Densified Fuel*; the Pellet Fuel Institute *Residential/Commercial Densified Fuel QA/QC Handbook*; and the *ALSC Residential/Commercial Densified Fuel Enforcement Regulations*:

**University of New Brunswick  
Canadian BioEnergy Centre  
1350 Regent St.  
Fredericton, NB E3C 2G6**

**506.453.4507  
Fax: 506.453.3574  
e-mail: cbec@unb.ca**

**Timber Products Inspection  
1641 Sigman Rd.  
Conyers, GA 30012**

**218.428.3583  
Fax: 770.922.1290  
e-mail: cwiberg@tpinspection.com**

**Twin Ports Testing  
1301 N. 3<sup>rd</sup> St.  
Superior, WI 54880**

**715.392.7114  
800.373.2562  
Fax: 715.392.7163  
e-mail: ssundeen@twinportstesting.com**

**University of Maine  
Forest Products Laboratory  
201 Nutting Hall  
Orono, ME 04469**

**207.581.2883  
Fax: 207.581.2875  
e-mail: Mehdi.Tajvidi@maine.edu**

**American Lumber Standard Committee, Incorporated**  
7470 New Technology Way, Suite F Frederick, MD 21703  
301.972.1700 fax 301.540.8004 e-mail: alsc@alsc.org www.alsc.org